



ESCLUSIVISTA
 PORFIDO VALLECAMONICA
 PORFIDO GIALLOGIOTTO
 PORFIDO GRIGIOVERDE

	26	Harmonised	EN 1341, 1342, 1343, 1469, 12057, 12058	
		Product: DOP 03-2026	Slabs, setts and kerbs of natural stone	
		Intended use:	Internal/external paving, flooring and cladding	
		Denomination:	EN 12440:	Porfido dell'Alto Adige
			Commercial:	Porfido Grigioverde
			Petrological:	Riolite Ignimbritica
		Place of origin:	Trentino Alto Adige - Italia	
PORFIDO F.LLI PEDRETTI SRL - Via Manzoni n°160 25040 ESINE (BS)				
Characteristics		Declares value	Test method	
Reaction to fire		Klasse A1	96/603 CE	
Durability of flexural strength	lower expected value	15,6 MPa	EN 12372	
	mean value	18,1 MPa		
	mean value later 56 frost cycles	16,6 MPa		
	mean value later 20 thermal cycles	16,5 MPa		
Compressive strenght	lower expected value	116 MPa	EN 1926	
	mean value	141 MPa		
Apparent density	mean value	2526 kg/m3	EN 1936	
Thermal resistance				
Abrasion resistance	maximum value	20,0 mm	EN 14157	
Water absorbtion	maximum value	2,3 %	EN 13755	
Release hazardous substances		NPD		

porfido f.lli pedretti srl
 25040 ESINE (BS) Italy
 via Manzoni, 160
 tel. 0364 360605 r.a. - 45178
 fax 0364 45193

info@porfidopedretti.com
 www.porfidopedretti.com
 P. IVA N. IT 00553290982 - Cod. SDI 7HE8RN5
 Reg. Imp. BS e C.F. N. 00303320170
 Cap. Soc. € 50.000,00 i.v.

